



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			QA125HLS		
MATERIAL			LENS-PC		
			HOUSING-PC		
			-		
COLOR OF LENS			RED(), AMBER()		
FLASHES PER MIN.			60 ~ 80		
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.2W	MAX. 1.650A
PROTECTION GRADE			WATER & DUST PROOF IP66		
CABLE ENTRY			ø10 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED STROBE LAMP LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-								
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY			APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK				J.K.HAN	3	2016.10.05	
	6~30	±0.1	±0.2	±0.5	±1		TITLE								
	30~120	±0.15	±0.3	±0.8	±1.5		QA125HLS OUTLINE DRAWING								
	120~400	±0.2	±0.5	±1.2	±2.5		MODEL								
400~1000	±0.3	±0.8	±2	±4	QA125HLS										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO.					
	10~50	±0°30'		±1°	±2°					QA125HLS_OUT					
	50~120	±0°20'		±0°30'	±1°	SCALE				SIZE	REV	SHEET			
	120~400	±0°10'		±0°13'	±0°30'	N/S				A4	00	1/1			



A4(297X210)