



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		STND100L-N	
MATERIAL		HOUSING-ABS	
		LENS-AS	
		-	
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()	
FLASHES. PER MIN		60 ~ 80	
USE VOLT.	CURRNET	DC12V ~ DC24V	MAX. 0.480A
		AC110V AC220V	MAX. 0.175A
VOLUME		MAX. 105dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF IP54	
CABLE ENTRY		ø10 LEAD HOLE	
COLOR OF HOUSING		MAKER STANDARD	
ACTION		LED STEADY / FLASHING LIGHT	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-		1		-	
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5			H.M.SEO	J.Y.KIM		J.W.KIM	3	2022.12.23
	6~30	±0.1	±0.2	±0.5	±1			TITLE					
	30~120	±0.15	±0.3	±0.8	±1.5			STND100L-N			MODEL		
	120~400	±0.2	±0.5	±1.2	±2.5			OUTLINE DRAWING			STND100L-N		
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				DWG. NO.			STND100L-N_OUT		
	10~50	±0°30'	±1°	±2°							SCALE		
	50~120	±0°20'	±0°30'	±1°							SIZE		
	120~400	±0°10'	±0°13'	±0°30'							REV		
											SHEET		
								N/S			A4		
								00			1/1		

A4(297X210)