



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			STND100LR			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN			120 ~ 140			
USE VOLT.	POWER LED	CURRNET	DC12V	1W	0.880A	
			DC24V		0.520A	
			AC110V		MAX. 0.170A	
			AC220V			
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20			
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4	TITLE		STND100LR OUTLINE DRAWING		MODEL		STND100LR			
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO.		STND100LR_OUT		
	10~50	±0°30'		±1°	±2°					SCALE		SIZE	REV	SHEET
	50~120	±0°20'		±0°30'	±1°					N/S		A4	00	1/1
	120~400	±0°10'		±0°13'	±0°30'									

**Qlight**

A4(297X210)