



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	S125SOL
MATERIAL	HOUSING-ABS
	LENS-PC
	REFLECTOR-HEAT RESISTING ABS
COLOR OF LENS	RED(), AMBER()
FLASHES PER MIN.	60 ~ 80
BATTERY CAPA.	2.4V
FLASHES PER MIN.	0.7Ah
CONTINUOUS OPERATING TIME WITH NO CHARGE	50Hr
PROTECTION GRADE	WATER & DUST PROOF IP54
COLOR OF HOUSING	MAKER STANDARD
ACTION	SOLAR CELL LED FLASHING LIGHT

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
	f	m	Ⓞ	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	1	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
Y.C.KO	J.H.PARK		J.K.HAN	3	2017.11.01
TITLE			MODEL		
S125SOL OUTLINE DRAWING			S125SOL		
DWG. NO.			S125SOL_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		

Qlight